

AccuTrace®

Cable Route Tracer



- **Peak- and null-tracing capability**
- **Traces and determines depth of any conductive line**
- **Traces energized or de-energized lines through inductive or conductive coupling**
- **Extremely lightweight receiver**

DESCRIPTION

The AccuTrace Cable Route Tracer consists of a transmitter, which energizes the line with a traceable signal, and a portable receiver, which detects the signal. The transmitter can energize the line either by magnetic induction from a built-in antenna or by direct conductive connection to the metallic line.

Energizing the line conductively provides increased tracing distance and minimizes signal coupling to other lines. Inductive coupling, which does not require a mechanical connection to the line, permits a buried line to be traced without uncovering or de-energizing it.

The transmitter provides a simple, LO/HI pushbutton to adjust the transmitted signal's strength, and a PULSE button for battery conservation and easy identification of the signal.

The receiver can be used to trace lines using either peaks (detection of the maximum signal) or nulls (detection of the minimum, or zero, signal).

The antenna is swivel-mounted for operation in vertical, horizontal or 45° mode used to calculate depth. The receiver provides audible and visual indication of detected signal strength. Simple controls adjust sensitivity and amplification, and a jack provides for audio output to an optional headset. Standard AA batteries provide up to 30 hours of continuous operation.

When the receiver is not in use, the telescoping handle retracts for convenient, compact storage.

APPLICATIONS

AccuTrace locates and traces any conductive line such as cable, pipe or metallic conduit. Depth of the line can be established quickly by taking advantage of the swivel-mounted antenna. Adding an optional ring clamp to the system provides a stronger inductive signal for tracing in areas with heavy cable activity. Blockages in water pipes such as sewer lines can be found with the use of an optional watertight capsule transmitter. A tape-on transmitter lets the operator locate collapsed duct work.

FEATURES AND BENEFITS

- Easy to use and simple to operate, this cable route tracer can be used successfully the first day in the field.
- Conductive coupling lets the operator discriminate between multiple utility cables in a common trench and trace the line of interest. Conductive tracing also increases tracing distance.
- Inductive coupling lets the signal be transmitted without a direct metal-to-metal connection. The operator can trace an energized cable using a distinctive transmitted signal. Also, cables that do not have exposed terminations can be traced with ease.
- Both peak- and null-tracing mode methods can be used during a single trace to ensure accuracy and speed. Null tracing is very fast and can be used to identify sharp direction changes. Peak tracing can be used to find the cable at the start of the trace and to identify cable location when conditions make null tracing ineffective.

- Superinductive circuitry allows, in the inductive tracing mode, the AccuTrace to trace longer lengths than any known competitor. If conditions such as cable depth make normal inductive tracing inefficient, the superinductor will produce a signal that the receiver can trace.
- The receiver picks up only the distinctive transmitted signal by filtering out electric noise and static.
- Extremely loud, adjustable audio output eliminates the need for headphones in noisy areas. This makes the AccuTrace more comfortable and easier to use than units requiring headphones and visual interpretation.
- Extremely lightweight receiver increases operator comfort when tracing long cables or when using for extended periods.



The ring clamp is optionally available.

SPECIFICATIONS

Depth Limit: 20 to 30 ft (6 to 9 m)
Range: 5 ft to 3 miles (1.5 m to 5 km)
Transmit Frequency: 116 kHz
Pulse Rate: 5 to 10 Hz

Output Voltage

Conductive Mode, No Load: 48 V peak-to-peak on HI, 27 V peak-to-peak on LO
Power Source: Eight AA, 1.5-volt alkaline batteries

Temperature Range

Operating: 32 to 158° F (0 to 70° C)
Storage: -149 to +174° F (-65 to +79° C)
Humidity: Moisture resistant

Dimensions

Transmitter

3.5 H x 4.75 W x 11 D in.
 (90 H x 120 W x 280 D mm)

Receiver (extended)

27 in. (680 mm)

Carrying Case

15 H x 19 W in. x 8 D
 (380 H x 480 W mm x 200 D)

Weight

Transmitter: 2 lb (0.9 kg)
Receiver: 2.5 lb (1.1 kg)
Accessory Kit: 1.75 lb (0.8 kg)
Carrying Case: 6 lb (2.7 kg)

ORDERING INFORMATION

Item (Qty)	Cat. No.
AccuTrace	656621
Included Accessories	
Accessory kit	
Superinductive transmitting circuitry	
Direct connection cable	
Ground rod	
Suitcase-style carrying case	
AA batteries (8)	
Operating manual	AVTM656621
Optional Accessories	
Ring clamp	656626
Watertight capsule transmitter	656627
Tape-on transmitter	656628

UK
 Archcliffe Road Dover
 CT17 9EN England
 T +44 (0) 1304 502101
 F +44 (0) 1304 207342

UNITED STATES
 4271 Bronze Way
 Dallas TX75237-1088 USA
 T 800 723 2861 (USA only)
 T +1 214 330 3203
 F +1 214 337 3038

OTHER TECHNICAL SALES OFFICES
 Valley Forge USA, Toronto CANADA,
 Mumbai INDIA, Trappes FRANCE,
 Sydney AUSTRALIA, Madrid SPAIN
 and the Kingdom of BAHRAIN.

Registered to ISO 9001:2000 Reg no. Q 09290
 Registered to ISO 14001 Reg no. EMS 61597

ACCUTRACE_DS_en_V10

www.megger.com
 Megger is a registered trademark